



Mid-Mountain Materials

THE FINAL BARRIER AGAINST ABRASION, CHEMICALS AND HEAT

ARMATEX® FLUOROELASTOMER COATED GLASS FABRICS

	FF 18	FF 32
Coating	Fluoroelastomer	Fluoroelastomer
Color	Various	Various
Sides	2	2
Weight, oz/sq yd, nominal	18	32
Thickness, inches, nominal	.018	.038
Standard Widths, inches	60	60
Roll Length, lineal yards	50	50
System Use Limit, °F • °C, Continuous		
Treatment Limit	500 • 260	500 • 260
Fabric Limit	1000 • 538	1000 • 538
Chemical Resistance		
Oils	Excellent	Excellent
Hydrocarbons	Excellent	Excellent
Flame Support Resistance		
	Excellent	Excellent
Water Penetration Resistance		
	Excellent	Excellent
CAN BE CERTIFIED TO		
MIL-C24576(SH)		
MIL-I-24244		
ASTM E 162	•	•
ASTM E84.84a	•	•
SUGGESTED USES		
Pad and Lagging Cloth	•	•
Weld Protection, light		
Weld Protection, heavy		
Equipment Covers		
Expansions Joints	•	•
Heat Absorptions Medium		
Flame Resistant Shields		

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control.