



Mid-Mountain Materials

THE FINAL BARRIER AGAINST ABRASION, CHEMICALS AND HEAT

ARMATEX[®] SILICONE RUBBER COATED GLASS FABRICS

	SF 32	SF 37
Coating	Silicone Rubber	Silicone Rubber
Color	Various	Various
Sides	2	2
Weight, oz/sq yd, nominal	32	37
Thickness, inches, nominal	.035	.035
Standard Widths, inches	38, 60	38, 60
Roll Length, lineal yards	50	50
System Use Limit, °F • °C, Continuous		
Treatment Limit	450 • 230	450 • 230
Fabric Limit	1000 • 538	1000 • 538
Chemical Resistance		
Oils	Good	Good
Hydrocarbons	Good	Good
Flame Support Resistance		
	Excellent	Excellent
Water Penetration Resistance		
	Good	Good
CAN BE CERTIFIED TO		
MIL-C-24576(SH)	•	
MIL-I-24244	•	•
ASTM E 162	•	•
ASTM E84.84a	•	
SUGGESTED USES		
Pad and Lagging Cloth	•	
Weld Protection, light	•	•
Weld Protection, heavy		
Equipment Covers		•
Expansions Joints	•	•
Heat Absorption Medium		•
Flame Resistant Shields		

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control.