



**Mid-Mountain Materials**

# THE FINAL BARRIER AGAINST ABRASION, CHEMICALS AND HEAT

## ARMATEX<sup>®</sup> SRS 40

ARMATEX<sup>®</sup> SRS 40 is a silica fabric impregnated with silicone rubber on one side to a finished weight of 40 oz/sq yd. An ideal product for heavy duty protection of equipment and personnel. ARMATEX<sup>®</sup> SRS 40 has a higher temperature capability base fabric than traditional welding fabric, and the coated material has excellent abrasion resistance.

### AVERAGE PHYSICAL PROPERTIES

Coating	Silicone Rubber – Coated One Side
Color	Red
Weight, oz/sq yd, nominal	40 (±10%)
Thickness, inches, nominal	.058
Widths, inches	36
Flame Resistance	Excellent
Tensile Strength, lbs/in, nominal	350
Oil and Hydrocarbon Resistance	Very Good
Abrasion Resistance	Excellent
Temperature Rating:	
Coating	450°F • 230°C continuous
Base Fabric	1800°F • 982°C continuous
Base Fabric can be certified to:	MIL-I-24244
SRS 40 (Coated Fabric) can be certified to:	MIL-I-24244
Standard Roll Size	50 LY

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control.